

Small Class | Product Overview

The hydraulic lift tables support ergonomic work and enable a workflow without height differences. Due to the low tare weight of 210 kg, the lifts are easy to move with a fork lift truck and location changing can be flexibly used.

STANDARD SPECIFICATION:

- Operating voltage 400 V
- „Dead man“ control by means of hand held pendant (cable length 1.2 m)
- Lower height limit switch
- All round contact trip switch
- Pipe rupture protection
- 2 maintenance chocks
- Table top made of plain sheet metal, painted
- Machinery Directive 2006/42/EG
- Complies with DIN EN 1570-1 (Lift category 1)
- Hydraulic unit and control system installed fixed on the base frame
- IP 54 protected

ADVANTAGES:

- Easy to install
- Immediately ready for use
- Continuous hydraulic height adjustment



Construction height: 205-260 mm



Lifting height: 900 mm

TECHNICAL DATA:

NAME	TYPE	LIFTING CAPACITY (KG)	LIFTING HEIGHT (MM)	PLATFORM DIMENSIONS (MM)	CONSTRUCTION HEIGHT (MM)	NET WEIGHT (KG)	PAINT
Lifting Table	S1	500	900	1,400 x 850	205	210	RAL 5015
	S2	500	900	1,700 x 1,200	205	210	RAL 5015
	S3	1,000	900	1,400 x 850	205	210	RAL 5015
	S4	1,000	900	1,700 x 1,200	205	210	RAL 5015
	S5	2,000	900	1,400 x 850	260	290	RAL 5015
	S6	2,000	900	1,700 x 1,200	260	290	RAL 5015

Lodge-LT-DS-Lifting_Tables_SmallClass-EN-20150226